



Interior & Exterior High Gloss Paint Formulation

with Borchi® OXY-Coat High-Performance Catalyst




New MEKO Regulation in the EU effective March 1st, 2022

GHS labeling will require 1B carcinogen with concentration limit at \geq 0.1%.

Borchi® OXY-Coat Formulation:

- Low VOC
- MEKO-Free
- Reduced Drier Complexity
- Cobalt-Free
- More Durable



- Standard Conditions (25°C, 50% RH)
- Adverse Conditions (10°C, 80% Humidity)

High Gloss, Interior & Exterior High Gloss Paint		
Material	Control Formulation	Borchi® OXY-Coat Formulation
Urakyd™ AD-130 Q-70	10.05	10.05
Borchi® Gen 1252 (100%)	0.15	0.15
Octa-Soligen® Calcium 10, basic	1.62	1.62
Tioxide TR 92	28.2	28.2
Exxol D60	3.45	3.45
Urakyd™ AD-130 Q-70	48.15	48.15
Exxol D40	8.38	8.38
TOTAL	100.00	100.00
10% Cobalt Drier	0.22	0.00
12% Zirconium Drier	1.79	0.00
Borchi® OXY-Coat - Cobalt-free	0.00	0.20
MEKO	0.50	0.00
EZ-Blox	0.00	0.50
TOTAL	102.51	100.70

Better Anti-Skinning Performance



Control

Borchi® OXY-Coat

Better Storage Stability



Control



Borchi® OXY-Coat

Higher Corrosion Resistance

Q-FOG Salt Spray After 330 h





Borchi® OXY-Coat



For more information, please reach us at borchers.com/contact

PLEASE NOTE: As each customer's use of our product may be different, information we provide, including without limitation, recommendations, test results, samples, care/labeling/processing instructions or marketing advice, is provided in good faith but without warrants and without accepting any responsibility/liability. Each customer must test and be responsible for its own specific use, further process ing, labeling, marketing, etc. All sales are exclusively subject to our standard terms of sale posted at www.milliken.com/terms (all ad ditional/different terms are rejected) unless explicitly agreed otherwise in a signed writing. Borchi is a trademark of Borchers Americas

